

# DC Standard Glasswashers

Introducing the new Standard Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



**Standard Range**  
SGP35 IS D  
SGP40 IS D  
SG45 IS D  
SG50 IS D

**Standard Extra Range**  
SXG45 IS D  
SXG50 IS D

- Fast
- Economical
- Energy Efficient
- Space Saving

*Plus: Extra loading height for taller glasses*

*Fitted with: Integral softener & Drain Pump*



## Performance

**Fast two minute wash cycle**  
ensures maximum productivity

**New innovative wash pump**  
increases wash pressure improving results

**Hydrodynamic basket slides**  
ensures optimum wash and rinse coverage

**Rinse thermo-lock**  
delivers perfect rinse temperatures time after time

**Dual element configuration**  
for faster start up and guaranteed wash temperatures (SX Range only)

## Energy and Cost Savings

**New innovative wash pump**  
saves 180W per hour

**Double skinned cabinet**  
reduces noise and heat emissions whilst lowering running costs

**Reduced water consumption**  
produces the optimum balance between water usage and hygiene

**Improved rinse arms**  
increases initial response by 30% and rotation speed by 20%

**Insulated boiler**  
lowers running costs and improves boiler recovery times (SX Range only)

## Operation

**Intuitive, simple controls**  
reduces user error and staff training

**EasyClean filters**  
maintenance friendly filters protect critical components

**Chemical auto-dosing**  
eliminates user intervention and prevents over or under dosing

**Auto drain down (optional)**  
ensures rapid drain down with no need for user intervention

**Integral water softener (optional)**  
softens water without the need for an external unit



## Standard Range Glasswasher Specifications

Extra loading height for taller glasses



	SGP35 IS D	SGP40 IS D	SG45 IS D	SG50 IS D
Cycle time	120 sec	120 sec	120 sec	120 sec
Baskets (x2)	350 x 350 mm	400 x 400 mm	450 x 450 mm	500 x 500 mm
Height	620 mm	670 mm	680 mm	680 mm
Width	420 mm	460 mm	515 mm	570 mm
Depth	470 mm	515 mm	555 mm	615 mm
Depth with door open	705 mm	795 mm	890 mm	950 mm
Usable wash height	210 mm	260 mm	310 mm	320 mm
Drain height	120 mm	120 mm	120 mm	120 mm
Drain Ø	25 mm	25 mm	25 mm	25 mm
Wash tank	11 lts	14 lts	18 lts	20 lts
Boiler	2.8 lts	2.8 lts	2.8 lts	2.8 lts
Water usage	2.4 lts p/c	2.4 lts p/c	2.4 lts p/c	2.4 lts p/c
Wash element	1.6 kW	1.6 kW	1.6 kW	1.6 kW
Boiler element	2.8 kW	2.8 kW	2.8 kW	2.8 kW
Total load	3 kW	3 kW	3.1 kW	3.1 kW
Amps required	18 Amps	18 Amps	18 Amps	18 Amps
Detergent dosing	Yes	Yes	Yes	Yes
Rinse aid dosing	Yes	Yes	Yes	Yes
Water connection	3/4 BSP	3/4 BSP	3/4 BSP	3/4 BSP
Required water pressure	2-4 bar	2-4 bar	2-4 bar	2-4 bar
Drain pump	INCLUDED	INCLUDED	INCLUDED	INCLUDED
Internal softener*	INCLUDED	INCLUDED	INCLUDED	INCLUDED

### Machine Chemicals

Premier glass detergent 5 litres  
 Premier rinse aid 5 litres  
 Water softening salt 10 kgs

Code: PGD-5  
 Code: RA-5  
 Code: SA-10



### Standard Extra Range Specifications

Energy-saving Technology

Dual element configuration  
 Innovative wash pump  
 Insulated boiler



	SXG45 IS D	SXG50 IS D
Total load	4.7 kW	4.7 kW
Amps required	20 Amps**	20 Amps**
All other data corresponds with	SG45 IS D	SG50 IS D

Where water hardness exceeds 100ppm a water softener is required.

\*Internal water softener is not suitable for hot water above 80°C. Softening capacity between regenerations is 125 litres @ 800ppm. Where water hardness exceeds 800ppm and the daily wash cycles exceed 40 per day an alternative softener may be required - please contact your supplier for further information.

\*\*Can be configured to operate on either 18A or 3Ph+N upon request.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.

CONTACT: Regal Gaming and Leisure, 139 Brookfield Place, Walton Summit Centre, Bamber Bridge, Preston. PR5 8BF T: 01772 69 42 56

