




Self Contained Icemakers



Introducing the self-contained icemaker range from DC. Crystalline ice on demand.

Classic Ice




Solid cubes of crystalline ice that cools quickly and melts slowly - suitable for bars, night clubs, pubs, restaurants, healthcare industries, educational facilities, hotels and supermarkets.



Model	Production kg's p/24hrs	Storage kg	Dimensions mm (inc feet) W x D x H	Drain Height mm (inc feet)	Amps Required	Warranty Years
DC20-4A	20	4	355 x 405 x 610	145	13	3
DC25-6A	25	6	390 x 520 x 640	145	13	3
DC30-10A	30	10	390 x 520 x 720	145	13	3
DC35-16A	35	16	496 x 630 x 785	240	13	3
DC45-25A	45	25	496 x 630 x 895	240	13	3
DC55-25A	55	25	496 x 630 x 985	330	13	3
DC70-40A	70	40	737 x 640 x 1025	345	13	3
DC100-60A	100	60	737 x 640 x 1115	345	13	3
DC130-65A	130	65	840 x 740 x 1175	345	13	3
DC155-65A	155	65	840 x 740 x 1175	345	13	3

Hollow Ice




Hollow cubes of crystalline ice that cools rapidly - particularly suited to hardwater areas due to the ice manufacturing process - suitable for bars, night clubs, pubs, restaurants, healthcare industries, educational facilities, hotels and supermarkets.



Model	Production kg's p/24hrs	Storage kg	Dimensions mm (inc feet) W x D x H	Drain Height mm (inc feet)	Amps Required	Warranty Years
DCP25-8A	25	8	385 x 468 x 692	135	13	3
DCP32-15A	32	15	495 x 580 x 797	261	13	3
DCP45-20A	45	20	495 x 580 x 907	261	13	3
DCP75-30A	75	30	733 x 596 x 1017	350	13	3

Granular Ice



Similar to crushed ice it's softer than cubes and chewable, while its mouldable qualities suit displays or packaging applications - suitable for cocktail bars, cafeterias, healthcare industries, carehomes, fast-food outlets, educational facilities, hotels, fishmongers, supermarkets, transport and processing operations.



Model	Production kg's p/24hrs	Storage kg	Dimensions mm (inc feet) W x D x H	Drain Height mm (inc feet)	Amps Required	Warranty Years
DCG60-10A	60	10	450 x 620 x 685	140	13	3
DCG90-20A	90	20	496 x 660 x 795	240	13	3
DCG90-30A	90	30	496 x 660 x 905	240	13	3
DCG150-40A	150	40	741 x 678 x 1035	345	13	3
DCG150-55A	150	55	741 x 678 x 1125	345	13	3

Ambient air operating temperatures:
Minimum = +10°C Maximum = +38°C
Water inlet connection: 3/4"

Waste connection: 21mm
Icemaker ventilation: 200mm to the rear,
50mm to the sides and top

Productions figures are based on a 20°C ambient operating temperature and 15°C water inlet temperature



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

